



TECHNICAL DATA SHEET

TZB-BB2

TZB-BB2 CONTAINS SPECIALTY PENETRANTS AND SURFACTANTS THAT LOOSEN AND LIQUEFY HEAVY GREASE DEPOSITS, THEREBY ASSISTING IN THEIR BIODEGRADATION.

Benefit of use:

- Keeps floats clean;
- Reduces grease build-up headaches;
- Prevents emergency blockage;
- Saves on line jetting;
- Lower grease disposal costs;
- Reduces odours.

SPECIFICATIONS

Description	Solid pink blocks
Packaging	2lb block in a mesh application bag, 4/case. 5lb block in a mesh application bag, 2/case.
Nutrient Content	Biological nutrients and stimulants
Bacteria Count	3 billion per gram
Storage and Handling	DO NOT FREEZE! Store in a cool dry location. Do not inhale dusts. Avoid excessive skin contact. See MSDS.



APPLICATION INSTRUCTIONS

Add TZB-BB2 directly to the lift station or oily sump.

When locating the block in the sump, do not place TZB-BB2 directly into the flow of incoming wastes. The turbulence and “washing effect” will greatly reduce the longevity of this product. Ideally, TZB-BB2 should be placed in a less turbulent area of the sump, but not in a dead spot.

TZB-BB2 should be suspended in the sump so that it is always submerged in water, even at the lowest water level. This will assure maximum contact time with the organics providing superior results.

If a grease shelf is present during placement of TZB-BB2, it is recommended to raise the high level flow so that the bacteria can attack the grease shelf from the top, bottom and sides.

Results should be obtained in four to eight weeks from the time of application. If grease shelves are present at the time of application, a longer period of time may be required to obtain results.

Pit Size	Maintenance
1 000 gallons	2 lb/month
5 000 gallons	5 lb/month
10 000 gallons	5-10 lb/month
20 000 gallons	10 lb/month

Dosage rate varies with flow rates, retention times and oil accumulation. This rate is for a typical industrial sump or pit.