



TECHNICAL DATA SHEET

TZB-DRAM

TZB-DRAM IS SPECIALLY FORMULATED AND PACKAGED FOR DIRECT ADDITION TO DRAINS AND GREASE TRAPS IN RESTAURANTS AND COMMERCIAL BUILDINGS.

Benefit of use:

- Keeps floats clean;
- Reduces grease build-up headaches;
- Prevents emergency blockage;
- Saves on line jetting;
- Lower grease disposal costs;
- Reduces odours.

SPECIFICATIONS

Description	Green color, free-flowing granular powder
Fragrance	Citrus
Packaging	400 water-soluble pouches/pail
Stability	Max. loss of 1 log/yr
pH	6.0 – 8.5
Bulk Density	0.5 – 0.61g/cm ³
Moisture Content	15%
Nutrient Content	Biological nutrients and stimulants, micronutrients and surfactants
Bacteria Count	1.5 billion per gram
Storage and Handling	DO NOT FREEZE! Store in a cool dry location. Do not inhale dusts. Avoid excessive skin contact. See MSDS.



TZB-DRAM contains microorganisms that are capable of degrading a wide range of animal and vegetable oils and greases under aerobic, facultative, anaerobic conditions. When applied on a regular basis, TZB-DRAM reduces the accumulation of grease in sumps, drains and traps. By degrading the grease, other solids are free to flow through the system.

APPLICATION INSTRUCTIONS

The application of TZB-DRAM should allow the maximum retention time in the drainage system. TZB-DRAM is supplied in water-soluble packaging for direct addition to the sewer system.

Kitchen Drains	1 oz. per day
Laundry Drains	1 oz. per day
Grease Traps	1 oz. per day

1. Use TZB-DRAM every night. The use of TZB-DRAM should be the last step in the nightly closing routine. Before starting TZB-DRAM it is recommended to have the drain lines rodded and the grease traps cleaned.
2. Stir one pouch of TZB-DRAM into 2 gallons of lukewarm water (~27-32°C., 80-90°F.). After a few minutes, most of the brown particles will settle to the bottom of the bucket, leaving the active ingredients suspended in the water. Please note that the particles will not dissolve when stirred.
3. Pour one medium-sized cup of TZB-DRAM solution down each Beverage Tower Drain.
4. Pour one medium-sized cup of TZB-DRAM down all floor drains.
5. Important: Pour the remaining solution of TZB-DRAM down the back sinks. For this procedure, the major portion of the liquid is required for maximum effectiveness on grease traps. Any remaining particles can be safely rinsed down the back sink drain with lukewarm water (~27-32°C., 80-90°F.).
6. Discard used cup. Wash hands after using TZB-DRAM. If a night is missed, use two packets the next day. Do not use hot water (over 54°C., 130°F.).