

TECHNICAL DATE SHEET

TZB-EDL

FORMULATED FOR THE TREATMENT OF DRAIN LINES AND DOWN LINES IN RESTAURANTS AND COMMERCIAL ESTABLISHMENTS.

TZB-EDL contains combined aerobic and anaerobic microorganisms, capable of biodegrading oil, dairy wastes, grease and a variety of organic materials in the thoughest conditions.

Benefits of use:

- Keeps drains and pipelines clean;
- Reduces grease accumulation;
- Reduces canalizing maintenance cost;
- Saves on line jetting;
- Reduces odors.

SPECIFICATIONS

Description	Red color liquid
Frangrance	Citrus
Packaging	1L, 4L, and 20L pails
рН	6.0 - 8.5
Temperature Range	10° – 63°C. (50° - 145° F.)
Nutrient Content	Biological nutrients and surfactants
Bacteria Count	79 million cfu/ml
Storage and Handling	DO NOT FREEZE! Store in a cool dry location. Do not inhale mists. Avoid excessive skin contact. See MSDS.



APPLICATION INSTRUCTIONS

Grease Traps – For less than 2 meter³ capacity, add 250ml of product daily by pouring in a sink or pipeline closest to the trap. This should be done at night or when the traps are used the least. After adding, flush down with a cup of lukewarm water.

For grease traps larger than 2 meter³, add 500ml daily using the same procedure.

Drain lines and down pipes - Use product a minimum of twice weekly to a maximum of 4 times depending on the usage of the building. Add product in amounts listed below by pouring directly into the drainpipe starting on the lowest floor and working up at a rate of one gloor each day. Do not treat same floor twice. When the top floor is reached, continue treating from the top floor only.

Pipe Size	Dosage	Frequency
50mm	100ml	twice/week
100mm	200ml	twice/week
150mm	300ml	twice/week
200mm	400ml	twice/week

DO NOT add TZB-EDL directly to grease traps; this practice is prohibited in most municipalites.